



60 LB. WASHER-EXTRACTOR

TOUCHSCREEN CONTROL ▪ UP TO 300 G EXTRACT ▪ FITS THROUGH A 3'- 0" DOOR



60 lb. capacity model 30022 V8Z

TOUCH SCREEN CONTROL FOR EASE OF USE AND FLEXIBILITY



MilTouch™ touch screen control, utilizing resistive touch screen technology and full VGA resolution, has a clear and informative display which shows current machine status info including total formula time and time elapsed. Formulas can be developed on a PC, saved to USB external memory and uploaded with a screen touch. Controller also provides intuitive fault diagnosis and relevant troubleshooting suggestions.

RinSave Water Saver Feature



The innovative RinSave® Water Saver process allows a precise high G-force to “sling” the wash liquor (including water, chemistry, and soil) out of the goods after a wash step – saving up to 2 rinses per load.



Industrial Frame

True 300 G Extract Rate When You Need It!

The 30022 V8Z offers a true 300 G extract rate. With a robust industrial frame, and a dedicated distribution speed, 300 G extract is achievable when you need it. Lower extract speeds are also available for uniforms, delicate textiles, and blended fabrics.

WASHER-EXTRACTOR SPECIFICATIONS

Capacity – lbs. (kg)	60 (27)
Cylinder Diameter x Depth – ins. (mm)	30 x 22 (762 x 559)
Door Opening – ins. (mm)	15.5 (394)
Cylinder Volume – cu. ft. (L)	9 (255)
Machine Dimensions (W x D x H) – ins. (mm)	34.5 x 56.5 x 58.68 (876 x 1436 x 1491)
Motor – HP (kW)	5 (3.72)
Wash Speeds – RPM	38-43
Distribution Speed – RPM	65
Extraction Speeds – RPM	420-840
Extraction G-Force	300
Inlet valve – ins. (mm)	.75 (19.1)
Drain valve – ins. (mm)	3 (76)
Approx. net weight – lbs. (kg)	1056

New, Superior Door Design

Door interlock allows for smooth handle opening and closing.



Fits through a 3'-0" doorway



NEMA Premium® efficient inverter-driven motor



Safe chemical injection



Pellerin Milnor Corporation
P.O. Box 400, Kenner, LA 70063 USA
Phone: (504) 712-7656
Toll Free: (800) 469-8780
Fax: (504) 468-3094
www.milnor.com
milnorinfo@milnor.com