



## 20-60 lb. VENDED WASHERS

QUALITY, VALUE, DURABILITY ■ FOUR CAPACITIES ■ EASY-TO-USE CONTROLS



20-25-lb. capacity model MCR12E5

# MILNOR cabinet-style washers are cost-effective for busy stores, and built for high profits and long life.

## MCR-model - a new look for MILNOR machines

These washers are designed by Milnor to deliver high profits, simple operation and the same legendary durability you would expect from their other machines.

## Wash big loads quickly

These frontloaders help customers wash quickly. A 20-25-lb. washer has a cylinder volume of 3.37 cu. ft.. The 35-lb. model features a 4.3 cu. ft. basket and the 45-lb. machine has a cylinder volume of 6.4 cu.ft. The 60-lb. washer has a large 9.0 cu. ft. basket for bulky or large loads. Three-compartment wash supply dispenser for liquid or powder chemicals is standard.

## Easy-to-use controls



Simple, easy-to-follow directions are printed in English and Spanish. A bright display counts down as coins are deposited. The display also counts down the number of minutes left in the total cycle, as well as the microprocessor's function (such as "add fabric softener" or "rinse") occurring at that moment. To help prevent downtime, the microprocessor identifies certain errors if they happen to occur. That way, the attendant can correct them. The formula count accumulator provides a load count. Milnor's microprocessor control delivers two sets of seven wash formulas, each with programmable vend prices. The first set features standard formulas ranging from a Quick Wash to a Heavy Soil option. **The second set of seven formulas uses Milnor's GreenTurn™ programming decisions, featuring fewer rinses, less hot water use and faster processing times. Either formula set can be selected by the store owner.**

## Superior washing quality

A reversing washing action means cleaner washing, with no tangling or knotting. This is the same lift-and-drop action that won Milnor its reputation for superior washing quality among commercial laundry operators. The proven single-motor inverter drive delivers a wash speed (reversing), load distribution speed (to minimize vibration during high-speed extraction) and final extraction.

## Choose from 4 sizes

Select the model that best meets your requirements and budget. The popular 20-25-lb. model is a great machine for any coin store. The 35-lb. washer is a great replacement machine for most competitive 30- and 40-lb. machines in the field. The 45-lb. and 60-lb. models are ideal for the larger part of your equipment mix.

## Suds overflow protection

Milnor machines help keep the floor dry with an overflow pipe (at rear). This reduces the danger of slipping.

## Easy-access gravity drain

There's no troublesome pump. Milnor's simple, gravity valve is front-mounted, drains quickly, and avoids clogging.

## Rugged vault deters theft

Great for unattended areas. Made of heavy gauge steel, the optional vault holds about \$100 in quarters. All wash formulas have different vend prices and are completely programmable.



45-lb. capacity model MCR18E4

## WASHER-EXTRACTOR SPECIFICATIONS

|                                       | MCR12E5         | MCR16E5         | MCR18E4         | MCR27E5         |
|---------------------------------------|-----------------|-----------------|-----------------|-----------------|
| Capacity - lbs. (kg)*                 | 20-25 (9-11)    | 35 (16)         | 45 (20)         | 60 (27)         |
| Cylinder diameter x depth - ins. (mm) | 23x14 (584x356) | 23x18 (584x457) | 28x18 (711x457) | 30x22 (762x559) |
| Gross cylinder vol. - cu. ft. (L)     | 3.37 (95)       | 4.3 (121)       | 6.4 (180)       | 9.0 (255)       |
| Motor - HP                            | 1               | 1.5             | 3               | 5               |
| Wash speed - RPM**                    | 32              | 32              | 32              | 32              |
| Distrib. speed - RPM**                | 64              | 64              | 64              | 64              |
| Extract - RPM**                       | 525             | 495             | 475             | 495             |
| Extract G forces                      | 90              | 80              | 90              | 100             |
| Drain valve - ins. (mm)               | 2 (51)          | 2 (51)          | 3 (76)          | 3 (76)          |
| Inlet valve - ins. (mm)               | .75 (19.1)      | .75 (19.1)      | .75 (19.1)      | .75 (19.1)      |
| Width - ins. (mm)***                  | 26 (660)        | 29 (737)        | 34.45 (875)     | 34.45 (875)     |
| Depth - ins. (mm)***                  | 31 (787)        | 36 (914)        | 43 (1092)       | 46 (1168)       |
| Height - ins. (mm)***                 | 42.4 (1077)     | 43 (1092)       | 52.63 (1337)    | 55 (1397)       |
| Approx. net weight - lbs. (kg)***     | 425 (193)       | 495 (225)       | 700 (318)       | 875 (398)       |

\* Depending on density and soil content of goods

\*\* Approximate

\*\*\* With standard accessories

Specifications and appearance subject to change without notice. Contact factory for acoustics data.



Pellerin Milnor Corporation  
 P.O. Box 400, Kenner, LA 70063 USA  
 Phone: (504) 712-7656  
 Toll Free: (800) 469-8780  
 Fax: (504) 468-3094  
 www.milnorcoin.com  
 mktg@milnor.com