



COIN-OPERATED DRYERS

RANGE OF SIZES • FAST, EFFECTIVE DRYING • TWO STYLE CHOICES



M330C



M50EDC

Optional stainless steel panels available.

MILNOR COIN-OP DRYERS. CHOICES FOR ANY LAUNDRY!

Classic-style dryers for any application

Milnor's classic-line of coin-op dryers feature unique advantages making them ideal for new store development or replacement of older, less efficient dryers. Easy-to-use controls and fast dry times make these dryers a popular choice among coin store customers.

	Capacity lbs. (kg)	Basket diameter ins. (mm)	Basket depth ins. (mm)	Basket volume cu.ft. (L)	Drive motor HP	Door opening ins. (mm)	Exhaust conn. ins. (mm)	Approx. width ins. (mm)	Approx. depth ins. (mm)	Approx. height ins. (mm)	Approx. net weight lbs. (kg)	Electric models Oven kW	Gas model voltages
M330C	2x30 (2x14)	27.25 (692)	30 (762)	2x10.2 (288)	2x.3	2x21.5 (546)	2x6 (152)	29.75 (756)	42.75 (1086)	78.25 (1988)	793 (360)	15	100-240V/ 1P/50,60C
M236C	2x30 (2x14)	27.25 (692)	30 (762)	2x10.2 (288)	2x.5	2x21.5 (546)	8 (203)	28.5 (724)	52 (1321)	76.25 (1937)	850 (386)	15	120-240V/ 1-3P/50,60C
M30C	30 (14)	32.75 (832)	25.63 (651)	12.5 (353)	.5	21.5 (546)	8 (203)	34.25 (870)	36.88 (937)	72 (1820)	534 (242)	20,24	120-240V/ 1P/50,60C
M50C	50 (23)	32.75 (832)	37.5 (953)	18.3 (518)	.75	21.5 (546)	8 (203)	34.25 (870)	49.75 (1264)	72 (1820)	651 (295)	20,24, 30	100-480V/ 1P/50,60C
M758C	75 (34)	36.25 (920)	36 (914)	21.5 (608)	1	31.38 (797)	8 (203)	38.25 (972)	47 (1194)	75.13 (1908)	721 (237)	30	120-575V/ 1P/50,60C
M78C	75 (34)	44.5 (1130)	24.88 (632)	22.4 (634)	1	31.38 (797)	10 (254)	46.19 (1175)	34 (864)	84.32 (2140)	888 (403)	24,36	120-575V/ 1P/50,60C
M4545C	2x45 (2x20)	32.75 (832)	30 (762)	2x14.6 (413)	2x.75	2x27 (686)	2x8* (254)	34.25 (870)	52.08 (1323)	81.1 (2059)	1015 (461)	N/A	120-240V/ 1-3P/50,60C
M115C	115 (52)	42 (1069)	41.25 (1048)	33.1 (937.29)	0.75	31.38 (797)	14 (356)	46.13 (1171)	63.56 (1614)	84 (2133)	1260 (572)	N/A	208-575V 3P/50,60C

*Optional 10" exhausts.

Specifications and appearance subject to change without notice.

EcoDry-style dryers for best efficiency

Milnor's ED dryers deliver unmatched energy savings combined with features that provide optimal drying performance. With 100% axial airflow, heat flows in from the rear and is captured in the solid steel drum where sensors efficiently manage heat.

	Capacity lbs. (kg)	Basket diameter ins. (mm)	Basket depth ins. (mm)	Basket volume cu.ft. (L)	Drive motor HP	Door opening ins. (mm)	Exhaust conn. ins. (mm)	Approx. width ins. (mm)	Approx. depth ins. (mm)	Approx. height ins. (mm)	Approx. net weight lbs. (kg)	Electric models Oven kW	Gas model voltages
M3030EDC	2x30 (2x14)	25.75 (654)	34 (864)	2x10.25 (290)	2x.25	19.38 (492)	2x6 (152)	27 (686)	40.63 (1032)	72.88 (1851)	535 (243)	N/A	120-240V/ 1P/50,60C
M3535EDC	2x35 (2x16)	30 (762)	30 (762)	2x12.27 (347)	2x.25	19.38 (492)	2x6 (152)	31.13 (791)	39.58 (1007)	80.38 (2041)	600 (272)	N/A	120-240V/ 1P/50,60C
M35EDC	35 (16)	30 (762)	30 (762)	12.27 (347)	.25	19.38 (492)	6 (152)	31.13 (791)	40.42 (1027)	67 (1701)	462 (210)	7.9- 13.5	120-240V/ 1P/50,60C
M50EDC	50 (23)	37 (940)	25.75 (654)	16.02 (454)	.75	27.38 (696)	8 (203)	38.25 (972)	40.13 (1019)	70.5 (1790)	610 (277)	18.5- 22	120-240V/ 1P/50,60C
M76EDC	75 (34)	37 (940)	35.5 (902)	22.09 (626)	.75	27.38 (696)	8 (203)	38.25 (972)	49.81 (1265)	70.5 (1790)	745 (338)	18.4- 20.4	120-240V/ 1P/50,60C
M5050EDC	2x50 (2x23)	2x32.75 (2x832)	2x32.75 (2x832)	2x16 (2x453)	2x.33	2x23.75" (2x603)	2x8 (2x203)	34.25" (870)	56.38 (1432)	83.75 (2127)	860 (390)	N/A	120-240V/ 1P/60C

Specifications and appearance subject to change without notice.



PELLERIN MILNOR CORPORATION
 P.O. BOX 400, Kenner, LA 70063
 504/712-7656
 Fax: 504/468-3094
 Literature Hotline: 800/469-8780
 Email: mktg@milnor.com
 www.milnorcoin.com

© Pellerin Milnor Corporation. Printed in U.S.A.
 B22SL07004/11092