

Simplifying Ownership

SUPERIOR AIRFLOW. IPSO small dryers and stack dryers produce fast-drying results with their advanced airflow pattern. Owners benefit from greater efficiency. But the real benefit comes from faster customer turnover and, as a result, greater profit potential.

SPACE SAVINGS. Choosing IPSO's stack units give owners the advantage of two dryers in the space of one. They gain extra capacity without the extra space.

LARGE CAPACITY. Our dryers boast a sizable cylinder capacity of 7.0 cu. ft. This enables small vended laundries to offer great drying capacity and performance in a small package.

TIME SAVINGS. The large, easy-clean lint filter is located upfront on the dryers, saving time and mess when it needs cleaning. In addition, the dryer's two-piece front panel makes servicing the unit a breeze — saving time and money.

PEACE OF MIND. Our commitment to you comes with a 3-year parts warranty.

HEAVY-DUTY SECURITY. IPSO's dryers deliver protection with a highly secure meter case. The case's design reduces the possibility of theft or vandalism.

SIMPLE CONTROLS. The dryers' simple controls make it easy to set and adjust vend prices.

Simplifying Customer Satisfaction

LARGE CAPACITY. With a capacity of 7.0 cu. ft., IPSO's dryer is ready to handle your customers' largest loads efficiently, enabling them to get in and out faster.



SIMPLE CONTROLS. IPSO's user-friendly control makes it easy for customers to start the machine. LEDs display when the machine is on a drying or cooling cycle.

EASY LOADING. Clients love the large door opening of 2.06 sq. ft., which makes loading and unloading a breeze.

THE BOTTOM LINE. Customers come to your store with one goal: to get in and out quickly. For applications where large capacity drying tumblers aren't the best fit, IPSO dryers offer an efficient alternative. From there, it's simply a matter of our dryers' speed and efficiency moving them out the door faster than your competition.

BDG909, BDE907
BSG909, BSE907



Commercial Single Load Dryer Specifications

	BDG909, BDE907 - Dryer		BSG909, BSE907 - Stack Dryer	
Height - in (mm)	43" (1092)		76 5/8" (1946)	
Width - in (mm)	26 7/8" (683)		26 7/8" (683)	
Depth - in (mm)	28" (711)		28" (711)	
Work Surface Height - in (mm)	36" (914)		N/A	
Cycles	Normal, Casual, Delicate, No Heat		Normal, Casual, Delicate, No Heat	
Basket Volume - cu. ft. (bar)	7.0 (198)		7.0 (198)	
Control(s)	Push-to-Start		Push-to-Start	
Motor HP (Capacitor Start and Thermal Protected)	1/3 HP, 5.5 amps		1/3 HP, 5.5 amps	
Motor - RPM	1725		1725	
Voltage/Hz/Phase Circuit Breaker - FLA	Gas: 120/60/1 Electric*: 120/240/60/1	15 30	Gas: 120/60/1 Electric*: 120/240/60/1	15 30
Top and Lid Finish	Porcelain		N/A	
Colors	White		White	
Net Weight - lb (kg)	140 (64)		275 (125)	
Crated Weight - lb (kg)	150 (68)		290 (132)	
Agency Approvals	UL, CSA Star		UL, CSA Star	

* Factory equipped 120/240/60/1 - may be field converted to 120/208/60/1 by qualified servicer.

For the most accurate information the installation guide should be used for all design and construction purposes. Due to continuous improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant. Features and certifications may vary by model.

©Copyright 2007 Alliance Laundry Systems LLC

Printed in the U.S.A.



Printed on paper manufactured with virgin pulp from certified sources and a minimum of 10% post-consumer recovered fiber.

Control Options



Dryer Coin Slide Control



Stack Dryer Coin Slide Control

Questions? Contact us at:
1 800 USA IPSO or www.ipsousa.com
1 800 (872-4776)

