

Simplifying Ownership

PROFIT POTENTIAL. Adding topload washers to complement larger washer-extractors ensures clients have a variety of options to fit their load size.

ENERGY EFFICIENT. The water-saver cycle on IPSO toploaders saves owners money by reducing hot water consumption, while trimming total water usage to 26.6 gallons compared to 33.5 gallons — the average for many older commercial toploaders.

LOWER COSTS. A 1/2 horsepower motor produces a 710 RPM spin speed. This keeps drying times and utility costs down, while getting customers in and out faster.

RUGGED RELIABILITY. Solid construction and heavy-duty components deliver the strength necessary for years of dependable service.

PEACE OF MIND. A 3-year parts warranty (5-years on major components) is standard.

SERVICEABILITY. In the unlikely event our machine requires service, IPSO toploaders are 100% front serviceable — meaning less down time.



Simplifying Customer Satisfaction

EASY TO USE. Clients appreciate the familiarity and ease of use topload washers present. In addition, they are great for washing small loads and enable customers to add that “forgotten” item after the cycle has started.

CLEAN RESULTS. A 210° wash stroke — the longest in the industry — contributes to customer satisfaction with excellent washing results.

TIME SAVINGS. Our fast 710 RPM final spin speed removes more water than many competitive models ensuring reduced drying times.

USER FRIENDLY. IPSO’s simple coin slide activation and basic control make operating the washer a breeze for your customers.



MAXIMUM PRODUCTIVITY. Customers don’t have to worry about frustrating cycle stoppages due to out-of-balance loads. IPSO washers are designed with superior out-of-balance protection to ensure cycles continue without stopping, keeping customers’ visits productive.

A CLEAN APPROACH. We believe laundry is a pretty basic chore, so why complicate it for your clients with confusing controls and activations. IPSO toploaders help you get customers in and out quicker — increasing their satisfaction and your profitability.

BWT920



BWT Series Topload Washer Specifications

BWT920

Height - in (mm)	43" (1092)
Width - in (mm)	25 5/8" (651)
Depth - in (mm)	28" (711)
Work Surface Height - in (mm)	36" (914)
Water Temperatures	Hot, Warm, Cold
Cycles	Normal, PP and Delicate
Basket Volume - cu. ft. (liters)	2.80 (79)
Water Pressure - psi (bar)	Pressure fill - 20 to 120 (1.4/8.3)
Spin Speed - RPM	2-spd: High 710, Low 474
Control(s)	E-mech/2-spd/Coin
Motor (Capacitor Start and Thermal Protected)	2-spd, 1/2 HP reversing for 1725 or 1140 RPM
Top and Lid Finish	Porcelain
Colors	White
Electrical Specifications	120/60/1 - 15 amp
Circuit Requirements	
Net Weight - lb (kg)	190 (86)
Crated Weight - lb (kg)	210 (95)
Agency Approvals	UL

For the most accurate information the installation guide should be used for all design and construction purposes. Due to continuous improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant. Features and certifications may vary by model.

©Copyright 2007 Alliance Laundry Systems LLC

Printed in the U.S.A.

 Printed on paper manufactured with virgin pulp from certified sources and a minimum of 10% post-consumer recovered fiber.

Control Options



Coin Slide Control

Questions? Contact us at:
 1 800 USA IPSO or www.ipsousa.com
 1 800 (872-4776)

