

Specifications

Models 472/482FGR & 472LSFG

Electrical connections		472/482FGR 472LSFG	
Voltage	120V 1PH 50/60Hz 5amps	Standard	
Voltage	230V 1PH 50/60Hz 25amps	optional	
Optional Iron Attachment:			
Voltage	120V 1PH 50/60Hz	Wattage	1000
	Approx. Consumption/hour		0.5 KWH
Steam and Air connection			
Steam Inlet	NPT	1/2"	
Steam Outlet	NPT	1/2"	
Rec. steam pressure	PSIG	75-85	
	kPa	517-588	
Steam consumption @ 80psig(552 kPa)	lb/hr	51.8	
	kg/hr	23.5	
Compressed air	NPT	3/8"	
Air consumption	free air/cycle at 80psig	0.32 FT ³	
	free air/cycle at 552kPa	.009m ³	
Rec. air pressure	PSIG	80	
	kPa	552	
Air Vacuum Connection	NPT	1 1/4"	
Weight (crated)			
Shipping	472/482 FGR	lbs	720
		kg	327
	472 LSFG	lbs	800
		kg	363

- | | |
|------------------------|---------------------------|
| 1 Control Push Buttons | 4 Steam Outlet connection |
| 2 Steam connection | 5 Air Vacuum Connection |
| 3 Air connection | 6 Electrical Connection |

Detail Line Drawing (millimeters shown in parentheses)

