

MULTI-JET

Deluxe compact cleaning machines with NITRO-JET SAFETY SYSTEM for Hydrocarbon, Silicone, RYNEX® and all other Class III-A solvents

Single Machines

with 35lb and
50lb capacities

Twin Machines

with 70lb and
100lb capacities



- **Newest advanced TRONIC-2 control system, with SUPER-3 microprocessor and P16 auxiliary board. Up to 20 automatic programs and easy to use manual controls, with lighted icons that indicate status of all machine operations.**
- **NITRO-JET SAFETY SYSTEM. Automatic safety nitrogen blanket that allows extra fast drying at full atmospheric pressure. This creates shorter cycles and more production.**



- Digital temperature control
- Automatic soap injector
- Inline solvent cooler for chilled water
- Durable stainless steel parts: drum, recovery section, button trap, filters and separators
- Tank to tank solvent transfer
- Self cleaning tanks
- Dry-Guard® self cleaning dry control
- Rapid-Dry® air flow drying system, with large chilled water condensing coil
- Double air filter with extra large surface
- Tank-Guard®, non-porous coating protection from metal corrosion
- Stainless steel tank reflectors
- Safety locks on all doors
- Adjustable wash/dry and extract speeds
- Floor-Guard® safety containment pan



Filter Systems

- Double Jumbo Cartridge Filter System with dual, independent solvent circuits
or
- New Nylon Disc Filter System for use with Tonsil, HYFLO®, Diatomite and other new filter aids. Complete with decanting filter and slide out tray for easy soil removal

MULTI-JET

290 N.E. 68St., Miami, FL 33138
Phone: 800-333-8883 Fax: 305-751-8390
www.drywetcleaning.com



MULTI-JET

7/01/03

SPECIFICATIONS: CLASS III – A SOLVENT MODELS			MJ 350
MAXIMUM LOAD CAPACITY		LBS.	35
CYLINDER:	Diameter	Inches	31.6
	Depth	Inches	23
	Volume	Cu. Ft.	10
	Wash Speed	R.P.M.	12-50
	Extract Speed	R.P.M.	540
	Door Opening Diameter	Inches	20
CAPACITIES:	Tank 1	Gal	20
	Tank 2	Gal	35
	Cartridge Filters (2)	Gal	44
	Spin Filter (Optional)	Gal	9
MOTORS:	Wash & Extract	HP	3
	Pump	HP	1
	Fan	HP	2
BRANCH PROTECTION:		AMPS	40
UTILITIES:	Electric: 208-240/60/3		
	¼" Compressed Air: 80-90 PSI	CFM	1.0
	¾" Water 50°F / 35-65 PSI	GPM	6
	½" Steam: 40-60 PSI	Size	½"
DIMENSIONS:	Width	Inches	39
	Depth	Inches	81
	Height	Inches	80
DYNAMIC CHARGE TO FLOOR:		#/sq. ft.	205
WEIGHTS:	Shipping	Lbs.	2800

All specifications subject to change without notice.

AERO-TECH USA, 290 NE 68TH Street, Miami, FL 33138
Tel (305) 754-4551 Toll Free (800) 333-8883 Fax (305) 751-8390
Website: www.steineratlantic.com E-mail: sales@steineratlantic.com